

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

Hazardous Substance, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Seal 'N' Flex FC**

Synonyms:

Seal 'N' Flex FC Black, 380 gram Cartridge
Seal 'N' Flex FC Black, 720 gram Sausage
Seal 'N' Flex FC Grey, 380 gram Cartridge
Seal 'N' Flex FC Grey, 720 gram Sausage
Seal 'N' Flex FC White, 380 gram Cartridge
Seal 'N' Flex FC White, 720 gram Sausage
Seal 'N' Flex FC Black (Export), 720 gram Sausage
Seal 'N' Flex FC Grey (Export), 720 gram Sausage
Seal 'N' Flex FC White (Export), 720 gram Sausage

Mancode

248673
248665
247235
247227
248703
248681
366331
366218
366323

Recommended use: Sealant, adhesive for construction application.

Supplier:	Bostik Australia Pty Ltd	Bostik New Zealand Limited
ABN:	79 003 893 838	
Street Address:	51-71 High Street Thomastown VIC 3074 Australia	19 Eastern Hutt Road Wingate Lower Hutt New Zealand
Telephone:	+613 9279-9333	+644 567-5119
Facsimile:	+613 9279-9342	+644 567-5412
Website:	www.bostik.com.au	www.bostik.co.nz

Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 243 622

2. HAZARDS IDENTIFICATION

AUSTRALIA CLASSIFICATION

This material is hazardous according to health criteria of Safe Work Australia.

Hazard Category:

Xn Harmful
Xi Irritant

Risk Phrase(s):

R42/43: May cause sensitisation by inhalation and skin contact.

Safety Phrase(s):

S23: Do not breathe vapour.
S24: Avoid contact with skin.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Poisons Schedule (Aust): Not applicable

NEW ZEALAND CLASSIFICATION

This material is hazardous according to health criteria of ERMA New Zealand

Product name: Seal'N'Flex

Substance Key: BOS0016502

Issued: 5 December 2011

Version: 3.1

Page: 1 of 7

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

ERMA Group Standard: Construction Products (Subsidiary Hazard) Group Standard 2006; HSR002544

HSNO Hazard Classification

- 6.5A Substances that are respiratory sensitisers
- 6.5B Substances that are contact sensitisers

Hazard Statement:

- H317 May cause an allergic skin reaction.
- H334 May cause allergy or asthma symptoms or breathing difficulties If Inhaled.

Prevention Statement:

- P103 Read label before use.
- P261 Avoid breathing vapour.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective clothing, gloves, eye/face protection and suitable respirator.
- P285 In case of inadequate ventilation wear respiratory protection

DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Diphenylmethane-4,4'-diisocyanate	101-68-8	<0.5%
Non-hazardous ingredients	-	Balance
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Notes to physician: Treat symptomatically. Effects may be delayed.

Product name: Seal'N'Flex

Substance Key: BOS0016502

Issued: 5 December 2011

Version: 3.1

Page: 2 of 7

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible material.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: Not applicable.

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

However for:

	TWA		STEL		CARCINOGEN	NOTICES
	ppm	mg/m3	ppm	mg/m3	CATEGORY	
Isocyanates, all (as -NCO)	-	0.02	-	0.07	-	Sen

As published by the Safe Work Australia or Department of Labour New Zealand.

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

WES-TWA (Workplace Exposure Standard – Time-weighted Average). The time-weighted average exposure standard designed to protect the worker for the effects of long-term exposure.

WES-STEL (Workplace Exposure Standard - Short-Term Exposure Limit). The 15-minute average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue changes, or necrosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply.

'Sen' notice - sensitiser. The substance can cause a specific immune response in some people. An affected individual may subsequently react to exposure to minute levels of that substance.

*** Medical supervision of all employees who handle or come in contact with respiratory sensitisers is recommended. Personnel with a history of asthma-type conditions, bronchitis or skin sensitisation conditions should not work with MDI based products.***

*** The Occupation Exposure Standards do not apply to previously sensitised individuals. Sensitised individuals should be removed from any further exposure.***

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the following ingredients in this material requires Health Surveillance:

Isocyanates.

For detailed information see "Guidelines for Health Surveillance (Safe Work Australia)"

Engineering measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Personal protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from polyvinyl alcohol (PVA) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Coloured thixotropic paste with aromatic solvent odour

Solubility:	N Av
Specific Gravity (20 °C):	1.26
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	43 (solids)
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	N Av
pH:	N App
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet)
N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Avoid high temperatures

Incompatible Materials: Water, alcohols, amines, acids and bases

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes - may include isocyanates.

Hazardous reactions: Will react exothermically with water and all organic compounds containing active hydrogen groups.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material may be irritant to mucous membranes and respiratory tract. A respiratory sensitiser. Can cause possible allergic reactions.

Skin contact: A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis. May cause skin sensitisation in sensitive individuals.

Eye contact: May be an eye irritant.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity

No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

Poisons Schedule (Aust): Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

This MSDS has been prepared by Chemcial Data Services Pty Ltd (www.chemdata.com.au) on behalf of its client.

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.bostik.com.au

Reason(s) For Issue: Change Logo

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Bostik Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.